

MASS FLOW CONTROLLERS

MASS FLOW CONTROLLERS

Thermal Mass Flow Controllers are designed to indicate and control set flow rates of gases.

The mass flow controller combines the characteristics, and accuracy of conventional mass flow devices into a unique compact design at low costs previously unattainable.

Each of these controllers incorporates an advanced U shape tube sensor in conjunction with flow passage elements constructed of aluminum and brass for non-corrosive gases or 316 stainless steel for corrosive applications. Zero and span adjustments are accessible from the outside of transmitters.

SPECIFICATIONS

	ACCURACY %FS				OPTIONAL ENHANCED ACCURACY %FS				
ACCURACY.	MODEL:	GC1, 3, 4	GC5, 6, 7		MODEL:	GC5, 6, 7			
AUGUNAUT:	FLOW RANGE:	0-100%	20-100%	0-20%	FLOW RANGE:	20-100%		0-20%	
	ACCURACY:	±1.0%	±1.5%	±3%	ACCURACY:	±1%	±1.0%	REF DATA with ±1%	
CALIBRATIONS: Performed at standard conditions [14.7 psia (101.4 kPa) and 70 °F (21.1°C)] unless otherwise requested. REPEATABILITY: ±0.5% of full scale. RESPONSE TIME: GC17: 300ms time constant; approximately 1 second to within ±2% of set flow rate for 25% to 100% of full scale flow. GC 37/47: 600ms time constant; approximately 2 seconds to within ±2% of set flow rate for 25% to 100% of full scale flow. GC 57/67/77: 1800ms time constant; approximately 5 seconds to within ± 2% of set flow rate for 25% to 100% of full scale flow. TEMPERATURE COEFFICIENT: 0.15% of full scale / °C.								otherwise requested. to 100% of full scale flow. to 100% of full scale flow. to 100% of full scale flow.	
PRESSURE COE PRESSURE DRO OPTIMUM GAS I	PRESSURE COEFFICIENT: 0.01% of full scale / psi (0.07 bar). PRESSURE DROP: See Table above. PTIMUM GAS PRESSURE: 05 main (1.70 harr).								
MAX. GAS PRES TURN DOWN RA MAX. DIFF. PRE GAS AND AMBIE MATERIALS ELLI	SURE: 1000 p TIO: 40:1. SSURE: 50 psi INT TEMP: 32 °F t	 E: 1000 psig (70 bars) maximum GC1, 3, 4. 500 psig (34.5 bars) GC5, 6, 7. 40:1. RE: 50 psi for GC1/3/5/6 and 7 (3.4 bars), 40 psi for 47 (2.7 bars). IEMP: 32 °F to 122 °F (0 °C to 50 °C). 14 °F to 122 °F (-10 °C to 50 °C) - Dry gases only. 							
 Aluminum models GC Series: anodized aluminum, 316 stainless steel, brass and FKM O-rings. b. Stainless steel models GC1S, 3S, 4S, 5S, 6S and 7S: 316 stainless steel and FKM O-rings. Optional O-rings: Buna[®], EPR and FFKM. ATTITUDE SENSITIVITY: OUTPUT SIGNALS: COMMAND SIGNALS: COMMAND SIGNALS: CONNECTIONS: Analog 0-5 Vdc or 4-20 mA for remote set point mode; NPN compatible purge /valve off. GC1: 1/4" compression fittings. Optional: 6mm, 3/8" and 1/8" compression fittings or 1/4" VCR[®]. GC3: 1/4" compression fittings. GC4: 3/8" compression fittings. GC5: 3/8" compression fittings. GC6: 1/2" compression fittings. GC7: 3/4" ENPT fittings. Optional: 3/4" compression fittings 									
LEAK INTEGRITY: 1 x 10 ⁻⁹ smL/sec of helium maximum to the outside environment. TRANSDUCER INPUT POWER: GC1, 3 and 4: Universal +12 Vdc to 26 Vdc, 650 mA maximum. GC5, 6 and 7: +12 Vdc, 800 mA; +24 Vdc, 650 mA optional. Circuit boards have built-in polarity reversal protection. Resettable fuses provide power input protection. DISPLAY: 3-1/2 digit LCD, 0.5" high characters.									
The selection of materials of construction, is the responsibility of the customer. The company accepts no liability.									

MASS FLOW CONTROLLERS



DESIGN FEATURES

- ✓ Rigid metallic construction.
- ✓ Maximum pressure of 1000 psig (70 bars) GC1, GC3, GC4. 500 psig (34.5 bars) for GC5, GC6 and GC7.
- \checkmark Leak integrity 1 x 10⁻⁹ smL/sec of helium.
- ✓ NIST traceable certification.

- ✓ Built-in tiltable LCD readout.
- \checkmark Local or remote set-point control.
- \checkmark 0-5 Vdc and 4-20 mA signals.
- ✓ Circuit protection.
- \checkmark Totalizer option.



	DIMENSION (INCH)									
MODEL	Compression Fitting	LCD VERSION						NO LCD	MOUNTING Hole	
	(except model GC7)	A	В	C	D	E	F	G	Н	J
GC1	1/4" Tube O Diameter	5.72	1.00	1.00	4.27	6.29	0.69	2.68	4.61	6-32
· · · · ·				*C	*D	*E				
GC3	1/4" Tube O Diameter	6.10	1.37	1.25	5.19	7.21	0.69	2.69	4.99	6-32
GC4	3/8" Tube O Diameter	6.10	1.37	1.25	5.19	7.33	0.69	2.69	4.99	6-32
GC5	3/8" Tube O Diameter	6.73	2.00	1.75	10.2	12.3	1.39	4.69	5.62	10-24
GC6	1/2" Tube O Diameter	7.55	3.00	3.00	10.24	12.4	2.5	6.80	6.53	1/4-20
GC7	3/4" NPT Female	8.66	4.00	4.00	10.5		3.0	6.80	7.55	1/4-20

GENERAL DESCRIPTION

Compact, self contained mass flow controllers are designed to indicate and control flowratesofgases. Therugged design coupled with instrumentation grade accuracy provides versatile and economical means of flow control. Aluminum or stainless steel models with readout options of either engineering units (standard) or 0 to 100 percent displays are available.

The built-in electromagnetic valve allows the flow to be set to any desired flow rate within the range of the particular model. The valve is normally closed as a safety feature to ensure that gas flow is shut off in case of a power outage. Set-points are controlled either locally or remotely.

The LCD readout built into the top of the transducer is tiltable over 90 degrees to provide optimal reading comfort. It is connected to the transducer by a standard modular plug, and is readily removable for remote reading installations. Transducers without LCD readout are offered for OEM applications.

The combined gas streams flow through a proportionating electromagnetic valve with an appropriately selected orifice. The closed loop control circuit continuously monitors the mass flow output and maintains it at the set flow rate.

Flow rates are unaffected by temperature and pressure variations within stated limitations.

Mass flow controllers are available with flow ranges from 10 sccm to 1000 sL/min N2. Gases are connected by means of 1/4", 3/8", or optional 1/8" compression fittings and 3/4" FNPT fittings. Optional fittings are available. These controllers may be used as bench top units or mounted by means of screws in the base. Transducer power supply ports are fuse and polarity protected.

MODEL	FLOW RATE	MAXIMUM PRESSURE DROP				
MUDEL	[std liters/min]	[psid]	[mbar]			
GC1	up to 10	1.06	0.075			
	20	2.00	0.138			
GC3	30	3.5	0.241			
	40	5.5	.379			
604	50	8	.551			
664	100	18.9	1.302			
GC5	200	10	690			
GC6	500	12	827			
GC7	1000	15	1034			

TABLE 45, MASS FLOW CONTROLLER ACCESSORIES					
MODEL NO.	POWER SUPPLIES				
6APSGCNA-12	Power Supply 110 vac/12 Vdc (North America)				
6APSGCNA-24	Power Supply 110 vac/24Vdc (North America)				
6APSGCEU-12	Power Supply 230 vac/12 Vdc (Europe)				
6APSGCEU-24	Power Supply 230 vac/24 Vdc (Europe)				
6APSGCAU-12	Power Supply 240 vac/12 Vdc (Australia)				
6APSGCAU-24	Power Supply 240 vac/24 Vdc (Australia)				
6APSGCUK-12	Power Supply 240 vac/12 Vdc (United Kingdom)				
6APSGCUK-24	Power Supply 240 vac/24 Vdc (United Kingdom)				
CABLE ASSEMBLY					
6ACBLGCD	Shielded cable assembly, 8ft long with 15 pin D-connector				
REMOTE READ OUT AND CABLE FOR REMOTE READOUT					
6ARLCDGM-3F	Remote LCD readout, with 3ft cable				
6ARCBLGM-3F	Remote cable, 3ft.				

RECHARGEABLE BATTERY KIT



Mass Flow Meter with Rechargeable Battery Kit

In many applications where line voltage is either not available or desirable, the mass flow meter can be used as a portable device. This is accomplished by using an external rechargeable battery kit.

The complete kit includes a battery, recharger and a compact carrying case with shoulder strap and belt loop. With the battery kit, the meter can be used in excess of 40 hours without recharging.

TABLE 45-1, MASS FLOW METER ACCESSORIES						
MODEL NO.	POWER SUPPLIES					
6APSGMNA-12	Power Supply 110 vac/12 Vdc (North America)					
6APSGMNA-24	Power Supply 110 vac/24Vdc (North America)					
6APSGMEU-12	Power Supply 230 vac/12 Vdc (Europe)					
6APSGMEU-24	Power Supply 230 vac/24 Vdc (Europe)					
6APSGMAU-12	Power Supply 240 vac/12 Vdc (Australia)					
6APSGMAU-24	Power Supply 240 vac/24 Vdc (Australia)					
6APSGMUK-12	Power Supply 240 vac/240 Vdc (United Kingdom)					
6APSGMUK-24	Power Supply 240 vac/240 Vdc (United Kingdom)					
BATTERY KIT WITH RECHARGER						
6ABPGMNA-12	Battery Kit, with recharger (110v)					
6ABPGMEU-12	Battery Kit, with recharger (220v)					
FEMALE 9 PIN D-CONNECTOR WITH CABLE						
6ACBLGM4-3F	Female 9 pin D-connector, with 3ft cable for connection to MDPC. (4-20 mA)					
6ACBLGM4-6F	Female 9 pin D-connector, with 6ft cable for connection to MDPC. (4-20 mA)					
6ACBLGM5-3F	Female 9 pin D-connector, with 3ft cable for connection to MDPC. (0 - 5 vdc)					
6ACBLGM5-6F	Female 9 pin D-connector, with 6ft cable for connection to MDPC. (0 - 5 vdc)					
REMOTE READ OUT AND CABLE FOR REMOTE READOUT						
6ARLCDGM-3F	Remote LCD readout, with 3ft cable					
6ARCBLGM-3F	Remote cable, 3ft. (additional cable lengths available) Contact Dakota®.					



DESIGN FEATURES

- ✓ Displays instantaneous, total and accumulated flow rates.
- ✓ Built-in Flow Linearizer (10 point linearization of the flow curve).
- ✓ Up to 47 different volumetric and mass flow engineering units.
- \checkmark Large 13mm (0.51") digits for flow rate and 5.5mm (0.21") for Total.
- ✓ Digital RS-232 or RS-485 interface (multi-drop capability of up to 64 devices.)
- ✓ Compact design for unit mount, panel mount, wall mount or field mount applications.
- ✓ User-programmable, optically-isolated pulse output.
- ✓ Two programmable, optically-isolated, digital outputs.
- ✓ Flow controllers, set point command control via local LCD or digital interface.
- ✓ Programmable set point table with ramping up/down capability up to 16 steps.
- ✓ Free Configuration and Monitoring Utility software.

Programmable Pulse Output

The programmable flow pulse output is operating independently from totalizers and based on configuration settings can provide pulse frequency proportional to instantaneous fluid flow rate.

The LCD/keypad and digital communication interface commands are provided to:

- ✓ Enable/Disable Pulse Output.
- ✓ Configure Pulse Output start flow rate (in % of full scale).
- ✓ Configure the Unit/Pulse value (in current volumetric or mass flow units).
- ✓ Configure Pulse Active On Time (10 6550 ms).

Applications

For flow meters and controllers with analog 0-5 (5-10) (0-10)Vdc, 4-20mA input output interface, where flow indications / control and totalizers or alarm functions are required. Also when re-transmission of the flow rate and/or totalizer functions via optically-isolated pulse output or serial communication is desired. Local or programmable set point control for flow controllers (no host PC presence required). Activation of user-supplied equipment via programmable optically-isolated digital outputs when flow alarms or totalizers events are active.

Display

The graphical LCD display has large 13mm (0.51") digits for flow rate and 5.5mm (0.21") for total and can be set by user to simultaneously show different combination of the flow parameters: flow rate, totalizers, flow alarms, and diagnostic events . All configuration parameter settings are easily accessed via a simple user-interface menu driven by a 6 button key-pad which can be password-protected.

Signal Input and Signal Output

- ✓ 0-5 Vdc (Input/Output)
- ✓ 5-10 Vdc (Output only)
- ✓ 0-10 Vdc (Input/Output)
- ✓ 4-20 mA (Input/Output)

For flow meters and / or flow controllers, TIO provides jumpers selectable for 0-5 Vdc or 4-20 mA analog set point control signals. The flow rate set point can be adjusted locally via key-pad, remotely via host PC using digital communication interface, or programmed in advance using built-in 16 steps batch table with ramping up/down support.

Digital Communication

All process data and settings can be read and modified manually via local LCD Keypad or through the digital RS-232 or RS-485 communication interface. Proprietary ASCII software interface command set and free Communication Utility software are provided.

46

Programmable Totalizers

TIO provides two independent programmable flow totalizers. Both totalizers are updated every 100 ms and can be set to activate different events. Main totalizer accumulated total is backed-up in EEPROM memory every second.

The LCD/keypad and digital communication interface commands are provided to:

- ✓ Enable/Disable totalizing the flow.
- \checkmark Start the totalizer at a preset flow rate (in % of full scale).
- ✓ Assign action at a preset total volume (Event Volume).
- ✓ Configure power on delay (in seconds).
- ✓ Configure Auto Reset at preset volume.
- ✓ Configure Auto Reset delay (in seconds).
- ✓ Reset the totalizer to ZERO.

Programmable Alarms

TIO provides the user with a flexible alarm/warning system that monitors the fluid flow for conditions that fall outside configurable limits as well as visual feedback for the user via the LCD or via an optically-isolated output. The flow alarm has several attributes which can be configured by the user via LCD/Keypad or digital communication interface:



- ✓ Enable/Disable flow alarm.
- \checkmark Low flow alarm settings (in % of full scale).
- ✓ High flow alarm settings (in % of full scale).
- \checkmark Flow alarm action delay.
- ✓ Flow alarm action latch mode.

SPECIFICATIONS

47

ADC/DAC RESOLUTION:	12 bit.
ANALOG INPUTS:	0-5 Vdc, 4-20 mA, 5-10 Vdc (jumper-selectable), 0-10 Vdc (special order).
ANALOG OUTPUTS:	0-5 Vdc, 4-20 mA (jumper-selectable).
LCD:	128x64 graphic LCD with instantaneous Flow reading and Total volume indication.
	Adjustable LCD contrast and back light.
KEY-PAD:	Local 6 tactical push buttons.
PULSE OUTPUT:	User-programmable, optically-isolated, with preset active low time interval (10 – 6550 ms).
DIGITAL OUTPUT:	Two programmable, optically-isolated, UCE @ 40Vdc, ICE @ 150 mA (Voltage Isolation: 250 Vrms).
DIGITAL INTERFACE:	RS-232 or RS-485 (multi-drop capability up to 64 devices).
PROTOCOL:	Proprietary ASCII software interface command set.
SPEED:	1200 - 2400 - 4800 - 9600 -19200 - 38400 - 57600 - 115200 baud (user selectable).
CONFIGURATION:	Stop bit: 1
	Data bits: 8
	Parity: None
	Flow Control: None
ADDRESSING:	Maximum 255 addresses (for RS-485 option only).
TYPE:	RS232 or RS485 2-wire.
POWER REQUIREMENTS:	12 – 26 Vdc (up to 60 mA maximum).
INTERFACE CONNECTORS:	Process I/O signals and Digital RS-232/RS-485 interface – miniature 9 pin female D-SUB connector.
	Digital optically-isolated outputs: TERM BLOCK HEADER 4POS 3.5MM Male Pins, Shrouded.
ENVIRONMENT:	Installation Level II, Pollution Degree II, (Per IEC 664).
ELECTROMAGNETIC COMPAT	IBILITY:
	Compliant ref. 89/336/EEC as amended. Emission Standard: EN 55011:1991,
	Group 1, Class A Immunity Standard: EN 55082- 1:1992
OPERATING TEMPERATURE:	-10 °C to +70 °C (14°F to +158 °F).
DIMENSIONS:	86.4 x 76.2 x 19.1 mm (3.4" x 3.0" x 0.75") - W x H x D.
WEIGHT:	Appr. 125g / 0.3 lbs.
The selection of mat	erials of construction, is the responsibility of the customer. The company accepts no liability.

٦

TABLE 49, TIO A	ACCESSORY'S				
MODEL NO.	DESCRIPTION	WHEN REQUIRED			
KIT-TM-DD	GM flow meter mounting kit, shielded cable with two 9 pins D-connectors for process signals and communication branch.	GM + digital communication with Host PC or PLC.			
KIT-TM-RD	GM flow meter mounting kit, 4 wire cable between GM RJ11 and TIO 9 pin D-connector.	GM (12 Vdc power option only), 5-10 Vdc input, no digital communication.			
KIT-TM-FD	GM flow meter mounting kit, flat wire cable between GM and TIO 9 pin D-connectors.	GM, 0-5Vdc input no digital communication.			
KIT-TC-110NA-2C	GC flow controller mounting kit, shielded cable with North America plug 110 Vac to 12 Vdc power supply, communication branch.	GC, 0-5 Vdc input, North America 12 Vdc power supply, digital communication.			
KIT-TC-110NA-2N	GC flow controller mounting kit, shielded cable with North America plug 110 Vac to 12 Vdc power supply.	GC, 0-5 Vdc input, North America 12 Vdc power supply.			
KIT-TC-110NA-4C	GC flow controller mounting kit, shielded cable with North America plug 110 Vac to 24 Vdc power supply, communication branch.	GC, 0-5 Vdc input, North America 12 Vdc power supply.			
KIT-TC-110NA-4N	GC flow controller mounting kit, shielded cable with North America plug 110 Vac to 24 Vdc power supply.	GC, 0-5 Vdc input, North America 24 Vdc power supply.			
KIT-TC-230EU-2C	GC flow controller mounting kit, shielded cable with EUROPE plug 230 Vac to 12 Vdc power supply, communication branch.	GC, 0-5 Vdc input, Europe 12 Vdc power supply, digital communication.			
KIT-TC-230EU -2N	GC flow controller mounting kit, shielded cable with EUROPE plug 230 Vac to 12 Vdc power supply.	GC, 0-5 Vdc input, Europe 12 Vdc power supply.			
KIT-TC-230EU -4C	GC flow controller mounting kit, shielded cable with EUROPE plug 230 Vac to 24 Vdc power supply, communication branch.	GC, 0-5 Vdc input, Europe 24 Vdc power supply, digital communication.			
KIT-TC-230EU -4N	GC flow controller mounting kit, shielded cable with EUROPE plug 230 Vac to 24 Vdc power supply.	GC, 0-5 Vdc input, Europe 24 Vdc power supply.			
KIT-TC-240AU-2C	GC flow controller mounting kit, shielded cable with AUSTRALIA plug 240 Vac to 12 Vdc power supply, communication branch.	GC, 0-5 Vdc input, Australia 12 Vdc power supply, digital communication.			
KIT-TC-240AU-2N	GC flow controller mounting kit, shielded cable with AUSTRALIA plug 240 Vac to 12 Vdc power supply.	GC, 0-5 Vdc input, Australia 12 Vdc power supply.			
KIT-TC-240AU-4C	GC flow controller mounting kit, shielded cable with AUSTRALIA plug 240 Vac to 24 Vdc power supply, communication branch.	GC, 0-5 Vdc input, Australia 24 Vdc power supply, digital communication.			
KIT-TC-240AU-4N	GC flow controller mounting kit, shielded cable with AUSTRALIA plug 240 Vac to 12 Vdc power supply.	GC, 0-5 Vdc input, Australia 24 Vdc power supply.			
KIT-TC-240UK-2C	GC flow controller mounting kit, shielded cable with UK plug 240 Vac to 12 Vdc power supply, communication branch.	GC, 0-5 Vdc input, UK 12 Vdc power supply, digital communication.			
KIT-TC-240UK -2N	GC flow controller mounting kit, shielded cable with UK plug 240 Vac to 12 Vdc power supply.	GC, 0-5 Vdc input, UK 12 Vdc power supply.			
KIT-TC-240UK -4C	GC flow controller mounting kit, shielded cable with UK plug 240 Vac to 24 Vdc power supply, communication branch.	GC, 0-5 Vdc input, UK 24 Vdc power supply, digital communication.			
KIT-TC-240UK-4N	GC flow controller mounting kit, shielded cable with UK plug 240 Vac to 24 Vdc power supply.	GC, 0-5 Vdc input, UK 24 Vdc power supply.			
KIT-TC-240UK-2AC	GC flow controller mounting kit, shielded cable with UK plug 240 Vac to 12 Vdc power supply, communication branch, analog 4-20 mA output branch from GC.	GC, 0-5 Vdc input, UK 12 Vdc power supply, digital communication, analog 4-20 mA output branch from GC.			
KIT-TC-240UK-4AC	GC flow controller mounting kit, shielded cable with UK plug 240 Vac to 24 Vdc power supply, communication branch, analog 4-20 mA output branch from GC.	GC, 0-5 Vdc input, UK 12 Vdc power supply, digital communication, analog 4-20 mA output branch from GC.			
KIT-TM	GM flow meter mounting kit, no cables.	GM, user-supplied custom cables.			
KIT-TC	GC flow controller mounting kit, no cables.	GC, user-supplied custom cables.			
CBL-DA9-X	9 conductor round shielded cable consisting of a 9 pin Female "D" Sub-Connector (plug) on one end, and loose wires on the other end.	For TIO stand alone option, user-supplied power supply.			

Г